



RFQ / SO#

2612 Howard Street
 Louisville, KY 40211
 TEL: +1 502-774-6011
 FAX: +1 502-774-6300
 Email: ttaftermarket@sypris.com

TRANSITION JOINT APPLICATION DATA SHEET

Date (dd/mm/yyyy)	Your Reference No.
Company	Contact Info.
Email	Telephone
Project Name	End Use Location

<u>Required Information</u>	<u>Item 1</u>		<u>Item 2</u>		<u>Item 3</u>	
Quantity						
Pipeline OD (NPS)						
Pipeline Wall Thickness						
Pipeline Wall Grade (1)						
Design Pressure						
Design Temperature						
MDMT (Min. Design Metal Temp)						
Type T or K (2)	T	K	T	K	T	K
Pressure Part Mat'l Cert.						
Construction Code						
Design Factor (3)						
Pups Required (4)	N	Y	N	Y	N	Y
Contents of Pipe						
Special Req.: (NDE, Origin, Coating, Special Contents, etc.)						

- (1) Material and Yield strength of component/equipment that TJ will be welded to.
- (2) Type "T" uses aluminum and SS flanges; Type "K" uses SS flanges and an aluminum stub end.
- (3) If not supplied, 0.72 DF will be assumed.
- (4) Customer supplied pipe.